









LED REFLECTORS BR Floodlights

Perfect Downlight with a small footprint

Easy-installation with standard bases and long ilfe means infrequent ongoing replacement. Perfect for recessed cans throughout the home, even in damp locations. Simple, dimming replacement LED bulb that offers the perfect combination of color temperature, brightness and beam angle for commercial and residential downlighting applications.

























DIMMABLE

| Model | Replaces | Lumens | ССТ | Bulb Shape | Beam Angle | UL Location Rating | UL Fixture Rating | Rated Life HOURS | Warranty YEARS | M.O.L. | M.O.D. | Case Quantity | ENERGY STAR |
|-----------------------|----------|--------|-------|---------------|---------------|-----------------------|----------------------|---------------------|-------------------|--------|--------|------------------|----------------|
| 7W R20 Floodlight | 50W | 550 | • • | R20 | 100° | Damp | Non-Enclosed | 25K | 3 | 3.8" | 2.5" | 24 | • |
| 8W BR30 Floodlight | 65W | 670 | • • • | BR30 | 100° | Damp | Non-Enclosed | 25K | 3 | 5.1" | 3.7" | 48 | • |
| 11W BR30 Floodlight | 65W | 850 | • • | BR30 | 100° | Damp | Non-Enclosed | 25K | 3 | 5.1" | 3.7" | 48 | • |
| 16.5W BR40 Floodlight | 85W | 1200 | 0 0 | BR40 | 103° | Damp | Non-Enclosed | 25K | 3 | 6.4" | 5" | 12 | • |

This lamp may not be compatible with all dimmers. Visit www.greenliteusa.com for dimmer compatibility information.



